


南京晟高新材料有限公司

NANJING SHENGGAO NEW MATERIALS INDUSTRY CO.,LTD




橡胶制品制造商 / 服务商

MANUFACTURER & SERVICE PROVIDER OF RUBBER PRODUCTS



公司简介 Company profile

南京晟高新材料有限公司是一家专业生产橡胶板、防滑垫、（PVC、PU、PE）输送带的企业，产品广泛应用于石油、化工、电力、船舶、造纸、机械制造、电子、包装、物流、木材、食品等行业。且能根据客户需要生产各种规格，特殊性能的橡塑制品，本公司技术力量雄厚，生产设备先进检测手段齐全售后服务完善，深受广大客户好评。



Nanjing Shenggao New Materials Industry Co.,Ltd is an enterprise specializing in the production of Rubber Sheet,Non-Slip Rubber Mat,PVC Conveyor Belt,PU Conveyor Belt and PE Conveyor Belt,the products are widely used in petroleum,chemical industry,electric power,shipping,paper making,machinery manufacturing,electronics,packaging,express logistics industry,wood,food and many other fields.And according to customer needs to produce various specifications,special performance of rubber&plastic products,the company has strong technical force,advanced production equipment detection means complete,perfect after-sales service,by the majority of customers.


质量 ● 价格 ● 交货期 ● 服务
Quality ● Price ● Deliveryt ● Service

目录 CATALOGUE




工业橡胶板系列

INDUSTRIAL RUBBER SHEET SERIES



防滑橡胶垫系列

ANTI-SLIP RUBBER MAT SERIES



输送带系列

CONVEYOR BELT SERIES



普通橡胶板 GENERAL(NR/SBR) RUBBER SHEET

- 特点：防水、防震、密封性
- 用途：密封件、橡胶圈及地面铺设

- Feature:Water-proof,shock -proof and sealing.
- Application:It can be used for sealing parts, rubber rings and flooring.
- Specification:



厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
NR/SBR	70±5	1.8	2.5	180	-25~+80
NR/SBR	70±5	1.6	3.0	200	-25~+100
NR/SBR	65±5	1.5	4.0	250	-25~+120
NR/SBR	60±5	1.4	5.0	300	-25~+120
NR/SBR	60±5	1.3	8.0	400	-25~+120
NR/SBR	50±5	1.2	10.0	600	-25~+120

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

氯丁橡胶板 NEOPRENE(CR) RUBBER SHEET



- 特点：阻燃性、耐油性
- 用途：垫圈、车间、防火场所
- Feature：Flame retardance and oil-resistance
- Application: It can be used for punching washers,workplace,fireproof place.
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm ³	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
CR RUBBER SHEET	70±5	1.6	3.0	200	-25~+120
CR RUBBER SHEET	60±5	1.5	4.0	250	-25~+120
CR RUBBER SHEET	60±5	1.4	5.0	300	-25~+120
CR RUBBER SHEET	50±5	1.35	6.0	350	-25~+120
CR RUBBER SHEET	40±5	1.3	8.0	400	-25~+120
FLAME RETARDANT CR	65±5	1.4	5.0	250	-25~+120
FLAME RETARDANT CR	70±5	1.5	4.0	200	-25~+120

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

丁苯橡胶板 SBR RUBBER SHEET



- 特点：耐磨、抗震、防水
- 用途：适合制作各种垫片
- Feature: Resistance of abrasion, shock resistance and good sealability
- Application: It's used for gasket and flooring.
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm ³	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
	70±5	1.6	3.0	200	-25~+100

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimension on the customer's request.



丁腈橡胶板

NITRILE (NBR) RUBBER SHEET



- 特点：耐油性、耐热性
- 用途：垫圈、油封、容器衬里
- Feature: Oil-resistance and heat resistance.
- Application: It can be used for punching washers,oil seals and container linings.
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
NBR RUBBER SHEET	70±5	1.6	3.0	200	-25~+120
NBR RUBBER SHEET	60±5	1.5	4.0	250	-25~+120
NBR RUBBER SHEET	60±5	1.4	5.0	300	-25~+120
NBR RUBBER SHEET	50±5	1.35	6.0	350	-25~+120
NBR RUBBER SHEET	40±5	1.3	8.0	400	-25~+120
HIGH GRADE NBR	60±5	1.3	≥ 10	400	-30~+120
HIGH GRADE NBR	70±5	1.35	≥ 8	350	-30~+120

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

丁基橡胶板 BUTYL RUBBER SHEET

●特点：气密性好、耐臭氧、耐热、耐老化、耐化学药品、吸震、电绝缘

●用途：防腐衬里

● Feature :Permeability to air ,ozone and heat resistance, anti-aging and chemical,shock absorption,electric insulation

● Application: It can be used for corrosion resistant linings.

● Specification:



厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
BUTYL RUBBER SHEET	70±5	1.5	5.0	250	-35~+120
BUTYL RUBBER SHEET	60±5	1.4	6.0	300	-35~+120
BUTYL RUBBER SHEET	50±5	1.3	7.0	350	-35~+120

备注 /Note:

①该类型产品可提供各种颜色 /All the colors available.

②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.

③该类型产品表面可以制成布纹效果 /Cloth impression finish available.

④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

三元乙丙橡胶板 EPDM RUBBER SHEET

- 特点：耐老化、耐臭氧、耐热、耐蒸汽
- 用途：桥梁工程、房屋防漏等特殊场合

- Feature: Anti-aging, ozone resistance, heat and steam resistance.
- Application: It can be used for bridge engineering, roofing and other special situations.
- Specification:



厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
EPDM RUBBER SHEET	65±5	1.4	5.0	300	-30~+120
HIGH GRADE EPDM	70±5	1.3	≥ 10	400	-30~+130

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

硅橡胶版 SILICON RUBBER SHEET



- 特点 : 无毒无气味、耐高温、耐老化
- 用途 : 用于医药、化工、电子、食品等行业
- Feature: Nonpoisonous and tasteless ,high-temperature resistance and anti-aging .
- Application: It can be used for pharmaceutical ,chemical,electrical and food processing industries.
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
SILICON RUBBER SHEET	60±5	1.25	7.0	350	-60~+200
SILICON RUBBER SHEET	50±5	1.25	7.0	350	-60~+200
SILICON RUBBER SHEET	40±5	1.25	7.0	400	-60~+200

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

高抗撕硅橡胶版 HIGH TEARING RESISTANCE SILICONE RUBBER SHEET

- 特点：高抗撕拉性、高延伸性、耐高温、耐老化、抗腐蚀
- 用途：用于医药、化工及食品行业
- Feature : High tearing resistance,high extensibility,high-temperature resistance and anti-aging .
- Application : It can be used for pharmaceutical ,chemical and food processing industries.
- Specification:




厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
High tearing resistance silicone rubber sheet	60±5	1.30	10.0	400	-60~+250

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s

氟橡胶板 VITON RUBBER SHEET



- 特点：最佳的耐油、耐高温、耐化学品腐蚀性能和抗老化性能
- 用途：冲制各种高耐油、耐高温腐蚀性强的密封件、密封圈、缸模衬里及航天、航空领域使用
- Feature：The best oil resisting, high-temperature resistance, anti-chemical corrosion and anti-aging resistance
- Application：Applied to punch all kinds of oil resisting, high temperature bearing products with high requirements, or pavement in the above occasions, also used in the tank lining in the corrosive chemical products.
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
VITON RUBBER SHEET	70±5	2.0	8.0	300	-30~+280
VITON RUBBER SHEET	70±5	2.0	10.0	350	-30~+280

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimension on the customer's request.

天然橡胶板 NATURAL (NR) RUBBER SHEET



- 特点：高弹性、高气密性、高强度
- 用途：密封垫、橡胶圈、地面铺设
- Feature：Strong elasticity, high air impermeability and high strength
- Application：It can be used for sealing gaskets, rubber rings and flooring materials.
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)	磨耗 Abration (mm3)
NATURAL RUBBER SHEET	40±5	1.1	22	600	-25~+100	80
NATURAL RUBBER SHEET	45±5	1.2	15	600	-25~+100	120
NATURAL RUBBER SHEET	50±5	1.2	12	500	-25~+100	120
NATURAL RUBBER SHEET	55±5	1.25	10	500	-25~+100	120
NATURAL RUBBER SHEET	60±5	1.30	14	500	-25~+100	120

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

耐油橡胶板 OIL-PROOF RUBBER SHEET

- 特点：耐油、耐腐蚀性、密封性、抗膨胀性
- 用途：冲制各种耐油类密封件，与油脂类接触的工作台面铺设

- Feature : Oil-resistance, anti-corrosion, good sealing and anti-expansion
- Application : It can be used to punch all kinds of sealing parts ,oil touching work table and ground.
- Specification:



厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
Oil-proof rubber sheet	65±5	1.5	3.5	280	-20~+100
Oil-proof rubber sheet	60±5	1.4	5.0	300	-20~+100

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

耐酸碱橡胶板 ACID & ALKALI BEARING RUBBER SHEET



- 特点：耐酸碱介质、抗腐蚀
- 用途：冲制各种用于有酸、碱介质的密封件
- Feature : Acid & alkali medium resistance and anti-corrosion
- Application : It can be used to punch all kinds of sealing for acid & alkali medium
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
Acid & alkali bearing rubber sheet	70±5	1.6	3.0	200	-25~+120
Acid & alkali bearing rubber sheet	65±5	1.5	3.5	280	-20~+100

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

耐寒热橡胶板 HOT & COLD BEARING RUBBER SHEET

●特点：良好的耐寒热性，高低温环境中工作
不易老化

●用途：用于冷藏车、库、汽管道密封件

● Feature : Good hot & cold bearing performance,good anti-aging feature under hot and cold surroundings

● Application : It can be used for sealing parts of refrigerator car, refrigerator storage and gas pipeline.

● Specification:



厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
Hot & cold bearing rubber sheet	65±5	1.5	3.5	280	-60~+150

备注 /Note:

①该类型产品可提供各种颜色 /All the colors available.

②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.

③该类型产品表面可以制成布纹效果 /Cloth impression finish available.

④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

彩色橡胶板 COLORIZED RUBBER SHEET



- 特点 : 防水、抗震、密封性
- 用途 : 用于铺设、胶垫、密封件等
- Feature : Water-proof, shock resistance and good sealability
- Application : It can be used for flooring, rubber mats and gasket seal.
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm ³	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
Colorized rubber sheet	70±5	1.6	3.0	200	-20~+100

备注 /Note:

- ①该类型产品表面可以制成布纹效果，便于粘贴 /Cloth impression finish available in order to stick easily.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该产品性能和尺寸可根据客户需求定制 /Specification and dimension on the customer' s request.

阻燃橡胶板 INFLAMING RETARDING RUBBER SHEET

- 特点：抗燃烧、离火自熄
- 用途：各种防火患场所及冰箱、空调主机使用

- Feature：Fire resistance,immediately self-extinguish after away from the fire
- Application：It can be used for fireproof sites,refrigerator and air conditioner.
- Specification:





厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	氧指数 Oxygen index
nflaming retarding rubber sheet	70±5	1.6	3.5	250	30

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

绝缘橡胶板 INSULATION RUBBER SHEET



- 特点 : 在介电环境中工作，最大绝缘电压 10 万伏
- 用途 : 用于变电所、发电厂、配电房等
- Feature : Work in the conductive surroundings,the maximum insulation voltage can reach 100000V.
- Application : It can be used for transformer station,power plant and electricity distributing station.
- Specification:


厚度 /Thickness	宽度 /Width	长度 /Length
3-80mm	500mm--1500mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	耐压 Withstand Voltage
Insulation rubber sheet	65±5	1.6	4.0	280	3KV-100KV

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该产品性能和尺寸可根据客户需求定制 /Specification and dimention on the customer' s request.

抗静电橡胶板 ANTI-STATIC (ESD) RUBBER SHEET



- 特点 : 弹性好、电极性好、排除静电干扰
- 用途 : 广泛用于电子、纺织、印染行业及要求较高的场所铺设
- Feature : Strong elasticity, good electric polarity, elimination of static interference
- Application : Widely applied as the pavement in the electronics, textiles and printing & dyeing industry with high requirements.
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	体积电阻率 Volume Resistance
Green Side	70±5	1.5	6.0	300	10 ⁸ -10 ⁹ Ωcm
Black Side	65±5	1.6	3.0	250	10 ³ -10 ⁵ Ωcm

备注 /Note:

- 该产品可做黑色、绿色、一面黑色一面绿色 /Black, green, one face is black and the other is green.
- ①该类型产品可提供各种颜色 /All the colors available.
- ②该产品性能和尺寸可根据客户需求定制 /Specification and dimension on the customer's request.

食品橡胶板 FOOD GRADE RUBBER SHEET



- 特点 : 无毒、无味、弹性好
- 用途 : 用于食品加工场所及食品行业工具配套件
- Feature : Poison and odor free, good elasticity.
- Application : Can be made as tool fittings used in the food-processing sites and food industry.
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm ³	伸拉强度 Tensile strength MPA	伸长率 Elongation %	颜色 Colour
Food grade rubber sheet	60±5	1.5	5.0	300	Red & white

备注 /Note:

- 采用无味、无毒原材料制作，无有害化学成分，色泽一致无污染。
- This kind of rubber sheet is made of poison & odor free raw material, no harmful ingredients to human beings, even luster and no pollution.

海帕隆橡胶板 HYPALON RUBBER SHEET

- 特点：耐臭氧性、耐老化性、耐化学腐蚀性
- 用途：医疗、化工、防腐材料
- Feature : Ozone resistance, anti-aging, chemical resistance
- Application : It can be used for medical and chemical industry, anti-corrosive material.
- Specification:




厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
Hypalon rubber sheet	60±5	1.4	6.0	300	-30~+120
Hypalon rubber sheet	50±5	1.3	7.0	350	-30~+120

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimension on the customer's request.


橡胶条 RUBBER STRIIP(SKIRTBOARD)



- 特点：机器裁剪、无接缝、多功能
- 用途：衬条、修补条、挡边条
- Feature :Cut by machine,seamless and multifunctional
- Application : It can be used for furring strip,repair strip and skirtboard
- Specification:

厚度 /Thickness	宽度 /Width	长度 /Length
1-100mm	10mm--3000mm	1-50m

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
RUBBER STRIIP(SKIRTBOARD)	80±5	1.6	3.0	200	-30~+120
RUBBER STRIIP(SKIRTBOARD)	70±5	1.5	4.0	250	-30~+120
RUBBER STRIIP(SKIRTBOARD)	60±5	1.4	6.0	300	-30~+120
RUBBER STRIIP(SKIRTBOARD)	50±5	1.3	8.0	350	-30~+120
RUBBER STRIIP(SKIRTBOARD)	40±5	1.2	10.0	400	-30~+120

NYLON INSERTION	COTTON INSERTION
	
EP CLOTH INSERTION	METAL MESH INSERTION
	
CLOTH FINISH	BRIGHT CLOTH FINISH
	



夹布、金属网（光面或者布纹面）橡胶板

CLOTH INSERTION & METAL MESH

(SMOOTH SURFACE &ROUGH SURFACE) RUBBER SHEET

●特点 : 有较强的拉伸强力、变形小

●用途 : 冲制密封件、轻型输送带

● Feature : Strong tense and small distortaion

● Application : It can be used for punching sealing parts and light conveying bells.

● Specification:


厚度 /Thickness	宽度 /Width	长度 /Length
1.5-100mm	10mm--3000mm	1-50m






Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
NYLON INSERTION	70±5	1.6	3.50	200	-30~+120
COTTON INSERTION	70±5	1.6	3.50	200	-30~+120
EP INSERTION	65±5	1.4	8.0	300	-30~+120
METAL MESH INSERTION	70±5	1.5	4.50	250	-30~+120
CLOTH FINISH	65±5	1.6	3.0	200	-30~+120
BRIGHT CLOTH FINISH	65±5	1.5	4.0	250	-30~+120

备注 /Note:

●所有夹层橡胶板可生产为一面光面一面毛面、布纹面、两面光面、两面布纹面

● All insertion rubber sheets can be smooth surface,rough surface,cloth marks surface,twin-smooth surface,twin-cloth marks surface to satisfy the requirements of the customers.

① Stud Rubber Mat	② Fine Ribbed Rubber Mat
	
③ Diamond Rubber Mat	④ Checker Rubber Mat
	
⑤ Flat Rubber Mat	⑥ Wide Ribbed Rubber Mat
	

⑦ Orange Rubber Mat	⑧ Corrugate Rubber Mat
	
UTE Anti-Slip Rubber Mat	Anti-Fatigue Rubber Mat
	
Anti-Fatigue Rubber Mat	Bubble Rubber Mat
	

▶▶▶▶ 防滑橡胶垫系列 ANTI-SLIP RUBBER MAT SERIES

- 特点 : 韧性好、防滑、抗震
- 用途 : 适用于天桥、车厢、体育场所、健身房、仓库等地面铺设
- Feature : Good elasticity, anti-slip and anti-shock
- Application : It can be used for overbridge, carriage, gymnasium, warehouse.
- Specification: ① - ⑧ Rubber Mat

厚度 /Thickness	宽度 /Width	长度 /Length
3-6mm	500mm--1500mm	1-50m

UTE Rubber Mat:

厚度 /Thickness	宽度 /Width	长度 /Length
10mm	914mm&1830mm	5m-50m

Anti-Fatigue Rubber Mat:

厚度 /Thickness	宽度 /Width	长度 /Length
15mm	900mm	1500mm
22mm	1000mm	1480mm
12mm	805mm	1010mm
12mm	914mm	1524mm
20mm	920mm	920mm

Bubble Rubber Mat:








厚度 /Thickness	宽度 /Width	长度 /Length
18mm	1000mm	1500mm

Properties Quality	硬度 Hardness ShoreA	比重 Density g/cm3	伸拉强度 Tensile strength MPA	伸长率 Elongation %	温度范围 Temperature range (°C)
① - ⑧ RUBBER MAT	65±5	1.5	3.5	250	-30~+120
UTE RUBBER MAT	65±5	1.4	5.0	250	-30~+120
Anti-Fatigue Mat	65±5	1.4	5.0	250	-30~+120
Bubble Rubber Mat	65±5	1.4	5.0	250	-30~+120

备注 /Note:

- ①该类型产品可提供各种颜色 /All the colors available.
- ②该类型产品根据性能需要可以夹纱布、尼龙布等 /Cloth insertion、nylon insertion available.
- ③该类型产品表面可以制成布纹效果 /Cloth impression finish available.
- ④该产品性能和尺寸可根据客户需求定制 /Specification and dimension on the customer' s request.

THE PATTERN CHOICE




布纹 (Fabric) 草带 (Grass) 粗棉布 (Thick cotton)			
波浪纹草带 (Wavy grass) 发丝纹 (Hair silking) 高尔夫纹 (Golf)			
毛毡 (Felt) 砂光机(方格) Sander(grid) 十字花纹 (Cross pattern)			
一字纹 (Linear shape) 鱼骨纹 (Herringbone) 圆凸头 (Cheese Head)			
链条纹(Card chain) 粗亚光 (Matt) 皮纹 (Dermatoglyph)			
细棉布 (Fine cotton) 直条纹 (Straight stripe) 钻石格 (Diamond lattice)			

食品级输送带是我们的主力产品之一。产品选用高强度优质聚酯 (Polyester) 织物作带芯，弹性好，不易变形，无污染，无异味，符合卫生指标，色泽适度，轻巧耐用。我公司生产的食品级输送带已广泛用于食品工业或粮食部门运输散装、听装、包装成箱的粮食、饼干、糖果、果蔬加工、家禽及肉类加工等相关行业。

FOOD GRADE CONVEYOR BELT

Is one of our main products. Products use high strength Polyester fabric (Polyester) with high quality as core, has good elasticity, not easy deformation, no pollution, no peculiar smell, in line with the health indicators, colour and lustre is moderate, light and durable.



The food grade conveyor belt produced by our company has been widely used in the food industry or grain department to transport grain, biscuits, confectionery, fruit and vegetable processing, poultry and meat processing and other related industries.



跑步机带从2004年开始进行跑步机带的研发，先后推出了多种规格的产品，从家用的薄型跑带到商用的厚型跑带，覆盖了全系列的产品。我们的产品先后通过了 ROHS、PAHS、REACH 等认证，完全符合欧盟、美国产品标准。通过多年的努力，已得到了广大客户的认可，成为值得信赖的跑带品牌。

TREADMILL BELT


Since 2004,the research and development of running belt has been carried out,and a variety of products have been launched,from thin running at home to thick running belt in business,covering the whole series of products.Our products have passed ROHS,PAHS,REACH and other certifications,and fully meet the European Union and American product standards.Through years of efforts,has been recognized by the majority of customers,become a trusted running brand.



电子行业我公司生产的电子行业用输送带无毒无味、抗静电、耐腐蚀、抗拉力强度高,产品材质有 PVC、PU、PE,并可根据客户要求加工订做，是电子生产行业首选的配套产品，具有横向稳定性良好适宜各种复杂环境下传输的特性。

ELECTRONICS INDUSTRY

The conveyor belt produced by our company is non-toxic and tasteless, anti-static, anti-corrosion, and high tensile strength. The products are made of PVC, PU and PE, and can be customized according to customer requirements. It is the first choice of supporting products in the electronic production industry.




木材行业使用的 PVC 型轻型输送带,应用于人造板生产线、地板生产线、百叶窗生产线和各种木工机械设备。皮带表面不同的材质、厚度及花纹决定皮带的附着力、物理、化学及机械特性。我们公司选取高强度织物来增加带体的耐磨性和强度。我公司产品带体结构的特殊性决定了它在实际使用过程中体现出的伸长率低,尺寸稳定,低噪音寿命长等。

WOOD INDUSTRY

PVC light conveyor belt used in wood industry, used in artificial board production line, floor production line, louver production line and various woodworking machinery equipment.

The adhesion, physical, chemical and mechanical properties of the belt are determined by different materials, thickness and patterns on the surface of the belt.


Our company selected high-strength fabrics to increase wear resistance and strength. The particularity of our product belt structure determines its low elongation, stable size, low noise and long life in actual use.



运输行业我们自主生产的物流行业用的高强度轻型输送带,具有自重轻、弹性好、延伸率小、使用寿命长、低噪音、安装方便、无污染等特点。目前已广泛应用在快递、机场、邮政速递、仓储中心等多个行业。根据不同的输送要求,制造加工出一系列适合物流输送皮带。

TRANSPORTATION INDUSTRY

The belt has the characteristics of light weight,good elasticity,small extension rate,long service life, low noise,convenient installation and pollution-free.At present,it has been widely used in many industries,such as express delivery,airport,postal express,storage center,etc.According to different transportation requirements,a series of suitable conveyor belts are produced.



橡胶产品生产车间 Rubber products workshop



输送带产品生产车间 Conveyor belt products workshop



南京晟高新材料有限公司

NANJING SHENGGAO NEW MATERIALS INDUSTRY CO.,LTD

TEL:+8618851956209/+8613813050234

WhatsApp:+8613813050234

EMAIL:njsghm@163.com/ymhsdb@163.com

Website: <http://www.njsghm.com>

ADD:NO.18 Songyuan Road,Gaochun Economic
Development Zone,Nanjing,China

